HITACHI Inspire the Next

CP-X340 series



- 1,500 ANSI lumens
 My Memory
- Native XGA resolution
 Whisper mode 31dB
- 5.5 lbs
 Supplied soft case
 RGB inputs and RGB
 Digital zoom (x4)
 output
 Freeze function
- Component/composite/
 Manual zoom & manual
- S-video inputs focus

 HDTV theater ready Kensington security slot
- FCC Class B
 Progressive scan
 16:9 mode
 My screen
- Reverse image function for ceiling mount
- Remote control

SPECIFICATIONS

Model name			CP-X340 series		
Liqui	d crystal panel	structure	0.7" polysilicon active-matrix TFT x 3		
Num	ber of pixels		786,432 pixels		
Reso	lution	Video	540 TV lines		
RGB			1024 dots x 768 lines		
Colo	rs		16.7 million colors		
Aspe	ect ratio		Native 4:3/16:9 compatible		
Lens			F1.7 - 1.9 manual zoom 1:1.2 manual focus		
Throw ratio (distance:width)			1.49 ~ 1.79 : 1		
Lamp			165W UHB		
Brightness			1,500 ANSI lumens		
Expected lamp life			Approx. 2,000 hours		
Contrast ratio			400 : 1		
Spea	akers		1W x 1		
Pow	er supply		AC100-120V/AC220-240V 50/60Hz		
Power consumption			240W		
Operating temperature			32°F ~ 95°F		
Inpu	Input signals RGB		VGA, SVGA, XGA, SXGA/UXGA (COMPRESSED), MAC13", MAC16		
	Composite video		NTSC, NTSC4.43, PAL, SECAM, PAL-M, PAL-N, PAL60		
		Component video	480i, 575i, 480p, 1,080i, 720p		
Acoustic noise level			37dB (31dB in whisper mode)		
H sync			15kHz ~ 91kHz		
V sync			50Hz ~ 120Hz		
Verti	cal keystone co	rrection	Digital keystone +/- 15°		
App	rovals		UL, C-UL, FCC Class B		
	RGB input	Analog RGB	15-pin D-sub connector x 2		
<u></u>	RGB output	RGB	15-pin D-sub connector x 1		
Input/Output terminals	Video input	S-video	Mini DIN 4-pin connector x 1		
tem		Composite video	RCA jack x 1		
brt		Component video	RCA jack x 3		
) Time	Audio	Input	Stereo mini jack x 2		
¥		Output	Stereo mini jack x 1 (RGB 1, Video and RGB2 use)		
르	Control terminals		9-pin D-sub connector x 1 (RS-232C control)		
			USB connector (USB mouse) x 1		
	Dimensions		11.7" x 2.5" x 9.2" (W x H x D)		
.0	Weight		5.5 lbs.		
Chassis	Supplied accessories		Remote control, batteries (AA), RGB cable, filter cover for		
ಕ			bottom-up use, power cord, operator/safety manual,		
			quick guide, soft case		
8=5	Lamp		CP335/345LAMP		
and and a	Remote Control		(Part #: HL01898)		
2					

CP-X340 series





Screen Size 4.3		Throw distance	
Diagonal*	Width*	Min*	Max*
30	24	35	42
60	48	72	85
80	64	96	114
100	80	120	143
120	96	144	172
150	120	181	216
200	160	242	288
300	940	363	433

Throw ratio: 1.49 ~ 1.79:1 (distance:width)

^{*:} Measured in inches

